

PANEL WAYPHONE

FEATURES

- Mobile (3G), fixed line (PSTN) telephone or Ethernet connectivity (VoIP)
- Extensive internal diagnostics, accessible locally or remotely
- Configure remotely using tone-dialling, optional on site via serial port
- Adaptive volume control and duplex operation
- Programmable send and receive levels
- External battery with charging options (solar, mains or remote power feed)
- Digitally stored announcements
- Response to remote user commands is by digitised voice
- Tilt/vandal detection and automatic dial up reporting
- Unique ID for location information
- One push button standard but can be expanded to three
- Lightning and radio frequency interference protection on PSTN / DC Feed Board
- Audible and visual feedback on button press with LED buttons
- Laser etched graphics which can be readily customized
- 2,5mm stainless steel face plate

TECHNICAL SPECIFICATIONS: PANEL WAYPHONE

Physical

Dimensions:
Standard: 220W x 480H x 850D(mm)
Customised sizes available

Environmental

Temperature range: -10 to +70 degrees C
Humidity: 95% non-condensing

Power Options

12V solar panel
Mains plug pack 15VDC 1A
Remote power feed 22V-70VDC
External 12V sealed lead acid battery

Network

PSTN or PABX
3G (GSM compatible)
Ethernet (VoIP)

Audio

Automatic volume control
Noise environments up to 105dBA
High clarity speaker to deliver up to 120dBA

User Interface

Hands-free operation
Push button(s) to call or play announcement
Illuminated push buttons (Optional)
Standard network tones

Configuration

Factory preset
Remote dial in
Management Software



Maintenance

Diagnostics via

1. Remote dial in
2. Remote PC based management system

Security

Four digit PIN protection

Automatic tilt/vandalism warning with dial up reporting

Supporting products

WayPhone Manager for control room call management

WayPhone Tester for automatic and remote testing

Warranty

12 months on parts and labour from date of delivery.