

ALDRIDGE





P-LED II - 30W



LED Lighting for Residential Roads



Dimensions



P-LED II - 30W

Features

- SmartCity Ready - TST compatibility Zigbee, LoRa, NBIoT
- High Performance Street Lighting luminaire designed to meet stringent Australian/New Zealand standards
- High Performance Optics designed to comply and meet Australian standards AS/NZS 1158.3.1:2020
- Direct replacement of 125W conventional P-category Mercury Vapour, Metal Halide, High Pressure Sodium and Fluorescent luminaires
- Integrated thermal management
- Segregated termination chamber c/w quick access latch
- Self cleaning housing and PMMA optical diffuser
- Aero screen diffusers (AE)
- 20 year design life
- 10 year warranty


Options

- **Controller:** Zhaga Book 18
- **DALI-2** D4i Driver
- **Fuse Terminal Block/FTB**
- **Surge Protection Device/SPD20KVA**
- **Class II/Double Insulated (DB)**
- **Colour:** Grey (GR Standard), Black (BL), White (WH),
- **CCT:** 4000K
- **Visor:** Glareshield/anti-spill light kit (GV)



Technical Data

- **Body:** High Pressure Marine Grade Die Cast Aluminum
- **Optics:** P4 & P5 Distribution
- **LED:** LUMILED
- **System Watts:** 30W
- **Finishing:** Powder Coat Grey (Grey Standard)
- **Mounting:** 4 - 9 Metres
- **Fixing:** Side Spigot Mount (27-35mm OD)
- **IP rating:** IP65
- **IK rating:** IK08
- **Voltage:** 100V - 240V 50/60Hz
- **Power Factor:** >0.9
- **Controller:** 7 Pin NEMA receptacle (std)
- **Surge Protection Device (SPD) :** 10KVa Standard



Specification P-LED II 30W

PRODUCT CODE	P30W.N7PBP
System Watts	30
Input Voltage	100V - 240V 50/60Hz
CCT (K)	2700/3000/4000
CRI	Ra>80
IP Protection	IP65
IK Protection	IK08
Weight (Kg)-max.	5.05kg