



FLEXIBLE & LED BOLLARDS (1300 88 SIGN



FLEXIBLE BOLLARDS

The DeNeefe **FLEXIBLE** Recycled Bollard is specially designed to prevent vehicles from parking on kerbs, paths, nature strips and other areas where parking is inadvisable.

This flexible bollard can be installed at car charging stations, walkways, pedestrian ramps, cycle lanes and parking lots. It provides passive safety and pedestrian protection.

DeNeefe's Recycled Bollard is made of non-toxic recycled materials and is non-flammable, with UV resistance. Recycled Bollard is also flexible; upon 90° impact it naturally bends and reforms back to the original shape. It has excellent resistant to external conditions including, chemicals, salt and rust. The Flexible Bollard also features ECE104 Class C compliant reflective tape.

THE **DNF-BF75** bollard can have text or logo embossed to indicate its use, and is available in 5 colours.

BOLLARD FEATURES

- EN 12767:2019 approved
- IP68 (LED Bollard)
- Made from non-flammable material
- Flexible
- Durable and impact resistant
- Non-toxic
- Fully recyclable
- UV resistant
- Contains fibreglass grid
- Available in several colours
- Surface or in-ground installation

APPLICATIONS

- Nature strips
- Walkways
- Cycle lanes
- Parking lots
- Charging stations
- Exit Ramps
- Bus turn
- Pedestrian ramps



NEW LED FLEXIBLE BOLLARD

The NEW DeNeefe **LED FLEXIBLE** Recycled Bollard has a **lifespan between 7 and 10 years**, thanks to the latest LED technology and the new high resistance batteries that contain and store solar energy far longer.

Powered by **8 solar-powered LEDs**, which comply with EN 1463-3, are the ideal road protection and lighting system at all points of the road network, making the LED Bollard visible at a distance of up to 500 meters.

BENEFITS OF LED BOLLARD

- No maintenance required
- Reducing the carbon footprint, (CO2 emissions)
- Instant Power Saving
- Immediate Amortization of the Investment
- Easy Installation, with no power supply necessary
- IP68
- EN 12767:2019 approved











AVAILABLE IN 5 COLOURS:

Dk Green Yellow Silver Grey

Red



Product	Description	Size & Weight				
Code		Height	Dia.	Base W	Weight	Product Image
DNF-LEDBK60	 Flexible LED Bollard EN12767:2019 Material vinyl nitril rubber blends, TPE Integrated fibreglass grid at bending point Can bend 90° without impacting the shape 8 solar-powered LEDs Visible up to 500 metres Lifespan 7 - 10 years with no maintenance * Anchorage Depth 200mm 	800mm	110mm	200mm	3.7kg	
DNF-BK60	 Flexible Bollard EN12767:2019 Material vinyl nitril rubber blends, TPE Integrated fibreglass grid at bending point Can bend 90° without impacting the shape * Anchorage Depth 200mm 	800mm	110mm	200mm	3.7kg	
DNF-BP60	 Flexible Bollard EN12767:2019 Material vinyl nitril rubber blends, TPE Integrated fibreglass grid at bending point Can bend 90° without impacting the shape 	600mm	100mm	220mm	3.2kg	
DNF-BPL75		700mm	110mm	220mm	3.9kg	
DNF-BF75	 Flexible Bollard EN12767:2019 Material vinyl nitril rubber blends, TPE Integrated fibreglass grid at bending point Can bend 90° without impacting the shape Can be embossed with logo as shown 	730mm	110mm	220mm	4kg	

Flammable Resistant

UV Resistant



DENEEFE SIGNS

320 Darebin Road Fairfield VIC 3078

www.trafficltd.com.au

NSW

P: +61 2 9736 3677 e: info@trafficltd.com.au

NT

P: +61 8 8947 0733 e: info@trafficltd.com.au

QLD P: +61 7 3266 1900 e: info@trafficltd.com.au VIC P: +61 3 9430 0222 e: info@trafficltd.com.au

ACT

P: +61 2 6299 7922 e: info@trafficltd.com.au

TAS P: +61 3 6273 1177 e: info@trafficltd.com.au

SA

P: 1300 88 7446 e: info@trafficltd.com.au

WA

P: +61 8 9248 1002 e: info@trafficltd.com.au

UNITED KINGDOM

P: +44 (0) 1159 223 797 e: info@aldridgetraffic.co.uk











Supplier